

DRI-SLIDE, INC -- PENETRATING OIL (VV-P-216C) -- 9150-00-261-7899

===== Product Identification =====

Product ID: PENETRATING OIL (VV-P-216C)

MSDS Date: 08/20/1985

FSC: 9150

NIIN: 00-261-7899

MSDS Number: BPTXR

=== Responsible Party ===

Company Name: DRI-SLIDE, INC

Address: 411 DARLING ST

City: FREMONT

State: MI

ZIP: 49412-1290

Country: US

Info Phone Num: 616-924-3950

Emergency Phone Num: 616-924-3950

Preparer's Name: RICHARD MADDEN

CAGE: 25707

=== Contractor Identification ===

Company Name: DRI-SLIDE, INC

Address: 411 DARLING ST

City: FREMONT

State: MI

ZIP: 49412-1290

Country: US

Phone: 616-924-3950

CAGE: 25707

===== Composition/Information on Ingredients =====

Ingred Name: NAPHTHENIC OILS, CATALYTIC DEWAXED HEAVY

CAS: 64742-68-3

RTECS #: PY8044500

Fraction by Wt: 28%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 5 MG/M3 (OIL MIST)

ACGIH TLV: 5 MG/M3 (OIL MIST)

Ingred Name: MINERAL SPIRITS

CAS: 64742-86-7

Fraction by Wt: 71%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS #: KW2975000

Fraction by Wt: <1%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: C 50 PPM

ACGIH TLV: C 50 PPM, VAPOR; 9293

EPA Rpt Qty: 1 LB

DOT Rpt Qty: 1 LB

Ingred Name: MONOBUTYL ETHER

CAS: 111-76-2

RTECS #:KJ8575000
Fraction by Wt: <1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHALATION OF HIGH
CONCENTRATIONS OF VAPOR MAY CAUSE CENTRAL NERVOUS SYSTEM
DEPRESSION. CHRONIC: PROLONGED OR REPEATED CONTACT MAY CAUSE
DEFATTING AND IRRITATION OF SKIN.
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:INHALED: COUGHING, WHEEZING, SHORTNESS OF
BREATH, DIZZINESS, DROWSINESS, NAUSEA, VOMITING, HEADACHE. SKIN:
DRY SKIN, REDNESS, SWELLING, ITCHING.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALED: MOVE TO FRESH AIR. GIVE RESPIRATORY SUPPORT AS
NEEDED. SKIN: WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE
DOCTOR. INGESTED: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL
HELP. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES WHILE HOLDING
EYELIDS OPEN. SEE DOCTOR.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:110F,43C
Lower Limits:0.9%
Upper Limits:6.0%
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, OR WATER
SPRAY/FOG
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
BUNKER GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDIZING
AGENTS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. CONTAIN
SPILL. DO NOT ALLOW MATERIAL INTO SEWERS OR WATERWAYS. WEAR PROPER
PROTECTIVE CLOTHING. RECOVER FREE LIQUID OR ABSORB WITH INERT
MATERIAL AND PLACE IN A CONTAINER FOR LATER DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DO NOT USE OR STORE NEAR SOURCES OF IGNITION OR INCOMPATIBLE
MATERIALS.
Other Precautions:AVOID BREATHING VAPORS. AVOID PROLONGED OR REPEATED
CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR IF
ENGINEERING CONTROLS FAIL AND DURING EMERGENCIES. USE SCBA IF USED
IN CONFINED AREA/ SPACE. USE RESPIRATORY PROTECTION IN ACCORDANCE
WITH 29 CFR 1910.134.

Ventilation:USE ONLY WITH ADEQUATE VENTILATION. IF USED, LOCAL EXHAUST
SHOULD HAVE >60 FPM.

Protective Gloves:NITRILE, PVA

Eye Protection:CHEMICAL SPLASH GOGGLES IF SPLASH LIKELY

Other Protective Equipment:USE CLOTHING TO PREVENT PROLONGED OR
REPEATED CONTACT.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRER CONTAMINATED CLOTHES BEFORE REUSE
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>350F,>177C

Melt/Freeze Pt:M.P/F.P Text:<-40F,<-40C

Vapor Pres:<10 MM HG

Vapor Density:4.8 (AIR=1)

Spec Gravity:0.82 (WATER=1)

Evaporation Rate & Reference:<0.1 (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:STRAW YELLOW COLOR, MINERAL SPIRITS ODOR

Percent Volatiles by Volume:72

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:SOURCES OF IGNITION OR CONTACT WITH
INCOMPATIBLE MATERIALS.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, FUME,
SMOKE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.